

APPOINTMENT OF A SUITABLE SERVICE PROVIDER TO PROCURE THE SUPPLY, INSTALLATION, AND COMMISSIONING OF THE QUALITY OF SERVICE (QoS) BENCHMARKING EQUIPMENT TO TEST THE NETWORK'S PERFORMANCE AND MONITOR QUALITY OF SERVICE OF THE MOBILE NETWORK OPERATORS' VOICE, DATA, VIDEO, MESSAGING SERVICES WITH SUPPORT AND MAINTENANCE FOR A PERIOD OF THREE YEARS.

1. Purpose of submission

1.1. The Authority intends to source through an open bid from eligible bidders to appoint a service provider to supply, install, and commission a Quality of Service (QoS) benchmarking equipment to test the performance and monitor quality of service of mobile network operators 'voice, data, video and messaging services with support and maintenance for a period of three years.

2. Background

- 2.1. ICASA is mandated to ensure the provision of good QoS by licensed telecommunication network operators and service providers.
- 2.2. QoS is described as the ability of a mobile network to provide a service at an assured service level. QoS is very critical in mobile communication network technologies including second generation (2G/GSM), third generation (3G/WCDMA), fourth generation (4G/LTE), fifth generation (5G), and Wi-Fi.
- 2.3. ICASA intends to source through an open bid from qualified bidders, a QoS Benchmarking Equipment that is comprised of a:
 - 2.3.1. Drive-test equipment;
 - 2.3.2. Walk-Test/Portable equipment (Backpacks);

- 2.3.3. Multi-vendor Post-processing tool; and
- 2.3.4. Scanner.
- 2.4. The proposed QoS Benchmarking Equipment will be used to monitor the performance of mobile services in South Africa in terms of service availability, accessibility (call setup), retainability (dropped calls), network coverage (signal levels), data throughput, latency and general quality of service.

3. Scope of the work

The scope of work entails the following deliverables:

3.1. **QoS Monitoring/Benchmarking Equipment**

- 3.1.1. ICASA seeks to acquire a QoS Benchmarking Equipment to monitor the quality of service for voice, data, video, messaging services.
- 3.1.2. The equipment shall be comprised of the following components/equipment:
 - a. Drive-test Benchmarking equipment with twenty-four (24) User Equipment (UEs), that can be setup to conduct measurements in 2G/3G/4G/5G/ Wi-Fi mode in an outdoor environment. **Note: One SUV vehicle will be provided by ICASA and must be setup with 24 UEs, one scanner and one inverter.**
 - b. Walk-Test/Portable equipment (Backpacks), with twenty-four (24) UEs that can be setup to conduct QoS measurements in 2G/3G/4G/5G/Wi-Fi mode in an indoor and outdoor environment. Four backpacks with capability to setup 6 UEs per backpack, and 4 ruggedized Tablets.
 - c. Scanner that can support 5G, LTE (FDD and TDD), LTE-A, UMTS/WCDMA, GSM, Wi-Fi technologies with scanning capability of 10 MHz 6 GHz frequencies, including up to layer 3 decoding for all the supported technologies.
 - d. Multi-vendor Post-processing Tool, that supports 2G/3G/4G/5G and Wi-Fi reporting and analysis. The tool should be compatible with logfile type formats; SQZ, NMF, TRP. The tool shall support three (3) perpetual user licences with support and maintenance for three (3) years from the contractual date, with an option to extend support. The Post-processing Tool shall be able to provide the analysis reports in a format specified by

ICASA, root cause analysis of QoS issues and identification of problem location.

- 3.1.2.1. Detailed specifications are provided in Appendix A.
- 3.1.2.2. The equipment shall record QoS events including blocked calls, dropped calls, signal levels, poor quality signals, low throughput thresholds, and other significant events related to QoS KPIs.
- 3.1.2.3. The configuration of the equipment must not only rely on network coverage availability but must be configured locally without relying on the internet.
- 3.1.2.4. The equipment shall be mobile, easily deployed, and transferable in different modes of transport (such as cars, public buses, etc.), or can be installed at a designated location to be specified by ICASA.
- 3.1.2.5. The equipment shall be able to store measurement data i.e., logfiles locally for processing and reporting. The frequency of upload of captured data shall be configurable. The equipment shall provide for manual upload as a redundancy mechanism to the auto-upload.
- 3.1.2.6. The equipment shall be able to monitor the following voice call scenarios:
 - a. Mobile to Fixed (M2F) subscriber;
 - b. Mobile to Mobile (M2M) subscriber;
 - c. Fixed to Mobile subscriber.
- 3.1.2.7. The test measurement scenarios of the equipment shall simulate typical end-user behaviour.
- 3.1.2.8. The equipment shall be able to:
 - a. Conduct voice, data, video, and messaging measurements for each mobile service provider.
 - b. Conduct the parallel measurements in (a) for each service provider.
- 3.1.2.9. The equipment shall support QoS testing of Voice, Data, Video, Messaging services offered in the different frequency bands as specified in the National Radio Frequency Plan (NRFP)¹ using technologies, including, but

_

¹ https://www.icasa.org.za/uploads/files/NRFP-Web_29032022.html

- not limited to GSM, EGSM, GPRS, EDGE, WCDMA (UMTS), HSUPA, HSPA+, HSDPA, LTE-TDD, LTE-FDD, LTE-A, Wi-Fi, VoLTE and 5G.
- 3.1.2.10. The bidder shall provide a comprehensive list of technologies supported by the proposed equipment which include GSM, EGSM, GPRS, EDGE, WCDMA (UMTS), HSUPA, HSPA+, HSDPA, LTE-TDD, LTE-FDD, LTE-A, Wi-Fi, VolTE and 5G.
- 3.1.2.11. The equipment shall support QoS tests for Voice, Messaging, Video and Data services in accordance with the "ICASA quality of service parameters" as specified in SANS-1725-1 (Voice Standard), SANS-1725-2 (Data Standard), and the End-User and Subscriber Service Charter regulations as well as the respective international standards including, but not limited to, ITU-T E.804, ITU-T P.863, ITU-T P.862.1, ITU-T P.861, and ETSI 102 250-2.
- 3.1.2.12. The equipment shall allow flexibility for users to customize key performance indicators (KPI), test cases, and report templates.
- 3.1.2.13. The equipment shall log and decode all protocol layer messages (Layer 1, Layer 2, and Layer 3) for all technologies supported.

3.2. Installation

- 3.2.1. The Drive-test equipment must be installed in an SUV vehicle that will be provided by ICASA and the installation shall comprise of 24 UEs, one scanner and one inverter. Vehicle installation will include but not be limited to the following: Cabling, Power Inverters, charging units, Antennas, GPS, and cabinets/racks/chassis with shock mountings to ensure a complete working equipment.
- 3.2.2. The Walk-test equipment must comprise of 24 UEs in four (4) Backpacks with six (6) UEs per backpack, and four (4) ruggedised Tablets, including supporting accessories.
- 3.2.3. The supplier shall provide software upgrade and installation of software patches at no additional costs to ICASA.
- 3.2.4. The commissioning and installation will take place at ICASA's Head Office (Centurion) or at premises that are agreed on by ICASA and the successful Service provider.

3.2.5. The equipment must include battery backup that is capable of running the equipment for at least 2 hrs while the vehicle engine is not running.

3.3. **Product Support**

- 3.3.1. The supplier shall have an online portal for logging faults and complaints and may supplement this portal with other reporting/interaction platforms.
- 3.3.2. All support for software/hardware required for the proper functioning of the equipment shall be valid for three (3) years after equipment acceptance.
- 3.3.3. The supplier shall provide licenses, remote/local upgrades of software, and installation of software patches for three (3) years from the date of installation of the equipment at no cost to ICASA for the proper functioning of the equipment.
- 3.3.4. The supplier must state the manufacturer's Original Equipment Manufacturer (OEM) end of support, and end-of-life for the proposed QoS Equipment, which shall not be less than 3 years from the date of installation. This must be supported by the product roadmap of the proposed equipment.
- 3.3.5. The supplier shall provide proof that they have support from the (OEM) regarding the availability of spares and repair facilities.
- 3.3.6. The supplier must provide a sample Service Level Agreement (SLA) indicating the turnaround time in providing the spares and the mean time to repair.

3.4. **Mandatory Requirements**

- 3.4.1. The bidder shall provide written proof that they are a registered and authorized OEM supplier or distributor of the proposed equipment in South Africa. Proof of three-year support and maintenance (written confirmation by OEM).
- 3.4.2. The bidder must have a local presence including an office in South Africa with technical support staff for providing level 1 troubleshooting support.

3.5. **Product Manuals and Technical description**

- 3.5.1. Manuals on the proposed equipment that guide on how to operate the equipment, conduct troubleshooting, and basic service maintenance of the equipment must be provided in soft and hard copy at the time of delivery of the equipment and shall be in English.
- 3.5.2. Technical description (schematics and equipment architecture) of the proposed equipment must be included in the response to this bid response.

3.6. Acceptance and Approvals

- 3.6.1. The supplier shall provide a checklist of items listed in 3.1 which will be signed by both parties upon delivery of the equipment components.
- 3.6.2. A full functional test, including a drive test and reports generation shall be conducted on the equipment after installation to confirm that it meets the requirements specified by ICASA.

3.7. **Training**

- 3.7.1. Within the context of this procurement, the supplier shall provide full training to a minimum of 20 officials of ICASA.
- 3.7.2. The training shall cover the functionality and maintenance of the equipment with practical hands-on sessions.
- 3.7.3. The training shall be done on the actual equipment being supplied under this bid.

3.8. Expected Components of the Equipment

- 3.8.1. The supplier is expected to provide ICASA with a QoS Benchmarking Equipment that consists of:
 - 3.8.1.1. Drive-test Benchmarking Equipment;
 - 3.8.1.2. Walk-test/Portable equipment;
 - 3.8.1.3. Multi-vendor Post-processing tool;
 - 3.8.1.4. Scanner;
- 3.8.2. The equipment should be able to measure the following mobile service KPI's: service availability, accessibility, retainability, service/network

coverage and quality of service as detailed in the technical specifications in Appendix A.

3.9. Monitoring progress on the assignment

3.9.1. The Project Leader shall perform the ongoing reporting and management of the Service Level Agreement (SLA) in accordance with the contract.

4. Proposed advertising period and recommended media

4.1. The bid will be advertised for 21 calendar days in the e-tender portal and ICASA's website on an 80/20 procurement principle.

5. Sourcing method

5.1. The service goods/service will be procured through an open bid in terms of ICASA's Supply Chain Management policy.

6. Briefing Session

6.1. A non-compulsory virtual briefing session will be conducted.

7. Qualification criteria

- 7.1. Bidders will be evaluated on Functionality based on the qualification criteria.
- 7.1.1. Bidders who fail to obtain cut-off score of 70 points for functionality will not be considered further for price and specific goals. Table 1 indicates the Bid Evaluation Criteria for functionality.
- 7.1.2. Only bidders who obtain the minimum qualification score will be evaluated in accordance with the 80/20 procurement principles as prescribed by National Treasury Regulations.

Table 1 Bid Evaluation criteria and weights

Table 1 Bid Evaluation Citteria and Weights				
A. Functionality:		Weight	Grading	
Prequalification criteria				
1. Proposed Project Plan The bidder provided a detailed project plan which include: (1) Gantt Chart which includes, Milestones such as Delivery schedule of equipment, integration plan, acceptance test plan with work breakdown structure. (2) Roles and Responsibilities Matrix/Diagram, (3) Project risks management with a mitigation plan, and (4) Quality control measures.		10	 5 = Project plan covers all 4 requirements 3 = Project plan covers requirements 1, 2 and 3. 1 = Project plan doesn't cover the requirements from 1,2 and 3, or no submission. 	
2. Conformance to t features of the te (Appendix A, Tab Test Equipment)	nder	15	The bidder complies as follows: • 5 = Complies to all 10 features. • 3 = Complies with features 1-9. • 1 = Doesn't comply with the features from 1-9 or no submission.	

3. Conformance to technical features of the tender (Appendix A, Table 3: Walk Test Equipment)	15	 5 = Complies to all 9 features. 3 = Complies with features 1-8. 1 = Doesn't comply with the features from 1-8 or no submission.
4. Conformance to technical features of the tender (Appendix A, Table 4: Multivendor Post Processing tool)	15	 5 = Complies to all 8 features 3 = Complies with features 1-8 1 = Doesn't comply with the features from 1-8 or no submission.

5.	Conformance to technical features of the tender (Appendix A, Table 5: Scanner)	10	 5 = Complies to all 10 features. 1 = Doesn't comply with all the features.
6.	Proof of three-year support and maintenance (written confirmation by OEM) from the Original Equipment Manufacturer (OEM) for the following requirements. 1. Ticket logging process 2. Troubleshooting, 3. Licenses management, 4. Software upgrades,	15	 5 = Proof of Support includes all listed requirements. 1 = Doesn't comply with all the requirements.

		
7. Provide reference letters		• 5 = Provide more than
with company letterheads		three (>3) testimonial
and contact details from		reference letters.
companies where the		
proposed or similar QoS		• 4 = Provide three (3)
Benchmarking Equipment		testimonial reference
was deployed or provided in		letters
the past 5 years.		
		• 3 = Provide two (2)
		testimonial reference
	10	letters
	10	
		• 2 = Provide one (1)
		testimonial reference
		letter
		• 1 = No submission of
		testimonial reference
		letters
8. Provide skills transfer plan	10	
which includes hands-on		
training, for a minimum of		5 = A skills transfer plan
twenty (20) ICASA staff		covering skills areas; a, b,
members with timeframes,		and c.
learning outcomes, and the		
objectives.		3 = A skills transfer plan
A skills transfer plan covering the		covering skills areas; a
following skills areas and hands-on		and b.
training on:		
(a)QoS Equipment & Configuration,		1 = A skills transfer plan
(b) Running Test Scripts for Voice		doesn't cover skill area a
, , , , , , , , , , , , , , , , , , , ,		or b,

and Data, (c) Support and maintenance procedures		or no skills transfer plan provided, or skill transfer plan provided without timeframes, Learning Outcomes, and the objectives.
TOTAL FOR FUNCTIONAL PRE- QUALIFICATION CRITERIA.	100	
B. Price	80	
C. Specific Goals	20	
TOTAL	100	

APPENDIX A

A.1. Drive Test Equipment

The equipment with Drive-test benchmarking equipment with twenty-four (24) User Equipment (UEs) that can be setup to conduct measurements in 2G/3G/4G/5G/ Wi-Fi mode in an outdoor environment. *Note: One SUV vehicle will be provided by ICASA and will be setup with 24 UEs, one scanner and one inverter.*

Table 2: Drive Test Equipment

Features	Description	Compliant	Non-Complaint
		(with supporting documents/details)	
1. Number of Devices	24 User Equipment		
2. Technologies	2G, 3G, 4G, 5G, and Wi-Fi		
3. Hardware	 a. Cabinet/Chassis/Rack/Probes with a Control Unit or UEs are mounted in Cabinet/Chassis/Rack/Probes. b. Scalable and Modular. c. Easily transferable to different vehicles. 		
4. Tracking	GPS positioning and trail mapping		
5. Input Voltage	10 – 19 V DC i.e., Equipment must be able to be powered using standard vehicle battery.		
6. Operation Mode	Local configurable to load, start or stop scripts.		
7. Dashboard	Real-time local monitoring of measurements including actual route trail and measurement events.		
8. Minimum Measurements Capability	 a. Data: Ping, FTP/FTPS DL/UL, HTTP/HTTPS, Network Performance Test, Video streaming and OTT applications. b. Voice Circuit Switch and VoLTE: Call Setup Success Ratio, Call 		

	Drop Ratio, Call Setup Time.
	C. Signal Strength and Quality for
	2G/3G/4G/5G/Wi-Fi
	d. Messaging: SMS Delivery Time
9. Inverter	12V DC 500 Watts Inverter
10. Battery	Minimum of 2 hours battery backup
Backup	at maximum configuration.

A.2. Walk Test Equipment (Backpack)

Walk-Test/Portable equipment (Backpacks), with twenty-four (24) UEs that can be setup to conduct measurements in 2G/3G/4G/5G/Wi-Fi mode in an indoor environment. A total of 24 UEs are required for the Walk Test equipment. Four backpacks with capability to setup 6 UEs per backpack, and 4 Tablets/Controllers (1 Tablet/Controller per Backpack).

Table 3: Walk Test Equipment

Features	Description	Compliant (with supporting	Non-Complaint
		documents/details)	
1. Number of Devices	24 UEs, 4 ruggedised tablets		
2. Technologies	2G, 3G, 4G, 5G, and Wi-Fi		
3. Number of	4		
Backpacks			
4. UEs in Backpack	UEs must be carried in Backpacks		
operational mode	for indoor and outdoor		
	environments.		
5. Operation Mode	Local configurable to load, start or		
	stop scripts.		
6. Dashboard	Real-time local monitoring of		
	measurements including actual		
	route trail and measurement		
	events, using a local controller		
	e.g., Tablet.		
7. Tracking	GPS positioning and trail mapping.		

8. Power supply	Backpacks with backup power	
	supply e.g., power banks	
9. Scalable and	Must be able to add more devices	
Modular	per backpack	

A.3. Multi-vendor Post Processing Tool

Table 4: Multi-vendor Post Processing Tool

Features/Description	Compliant	Non-Complaint
	(with supporting	
	documents/details)	
1. Multi-vendor and Multi technologies post processing		
tool i.e., it must be able to process logfiles from the		
following QoS benchmarking equipment which are;		
TEMS (Infovista), SwissQual, Nemo (Keysight) and		
other reputable QoS benchmarking equipment. The		
tool should be compatible with logfile type formats;		
SQZ, NMF, TRP. Supports the technologies 2G, 3G, 4G,		
5G, and Wi-Fi.		
2. Three (3) perpetual licences.		
3. Drill-down ability to analyse root cause failure e.g., Call		
Failure		
4. Supports analysis of ETSI KPIs, e.g., Drop Call Ratio,		
Call Setup Success Ratio, Call Setup time, Data		
throughput and Latency.		
5. Multiformat Report support, e.g., Excel-based reports,		
Customization capabilities for reports and analysis		
workbooks.		
6. Support Data visualization on maps such as Open		
Street Maps, Google Maps etc.		
7. Fully automatic benchmarking reports generation		
8. Interactive web-based dashboards.		

A.4. Scanner Receiver

Table 5: Scanner Receiver

Featu	es/Description	Compliant (with supporting documents/ details)	Non-Complaint
1.	Band Range: 10 MHz – 6 GHz		
2.	Supported Technologies : 5G, LTE (FDD and TDD), UMTS/WCDMA, GSM, Wi-Fi		
3.	Simultaneous Multi-Technology Measurement		
4.	Automatic Channel Detection or Mobile Blindscan		
5.	4G/5G Dynamic Spectrum Sharing (DSS)		
6.	Spectrum analysis and channel power measurements		
7.	SIB and MIB Decoding		
8.	LTE MIMO Measurements (2x2 and 4x2)		
9.	Layer 3 Measurements: 5G, LTE (FDD and TDD), WCDMA, GSM		
10	Number of channels (LTE/UMTS) 24		